

Internal Combi Boilers Product Range

Envirogreen™ Combi HE



ERP Rating



Envirogreen™ Slimline Combi



ERP Rating



Envirogreen™ Model

Envirogreen™ Model	Product Code	Heating Output Max.	Hot Water Flow Rate Ltr/min*	Seasonal Efficiency Rating**	Weight kg	ERP Rating		Dimensions (mm)		
						Heating	Hot Water	H	W	D
Envirogreen™ Combi HE C20	ECE020DLX	20kW	16	93.0	167	A	B	845	595	614
Envirogreen™ Combi HE C26	ECE026DLX	26kW	16	93.0	170	A	B	845	595	614
Envirogreen™ Combi HE C35	ECE035DLX	35kW	20	93.0	173	A	B	845	595	614
Envirogreen™ Slimline Combi C20	ECE020SLM	20kW	12-14	93.0	165	A	B	855	520	600
Envirogreen™ Slimline Combi C26	ECE026SLM	26kW	16	93.0	168	A	B	855	520	600
Envirogreen™ Slimline Combi C35	ECE035SLM	35kW	16	93.0	172	A	B	855	520	600

Firebird Condensate Pump available for use with all Firebird boilers.

* Litres per minute at a temperature of 40°C Δt. Where water demand exceeds this, a flow restrictor is recommended to ensure a water supply at an adequate temperature

** ErP 2015 Seasonal Efficiency. Source: www.ncm-pcdb.org.uk/sap